



www.premiercoatings.com

PRODUCT DATA SHEET

Headcorn Road · Smarden · Ashford · Kent · TN27 8PJ · United Kingdom
Telephone: + 44 (0) 1233 770 663 · Fax: + 44 (0) 1233 770 633
E-mail: enquiries@premiercoatings.com

PREMSEAL PRIMER

DESCRIPTION A black mobile liquid used in conjunction with Premseal Waterproof membrane in order to consolidate the substrate and ensure complete bond development.

COMPOSITION A blend of bitumen and hydrocarbon solvent.

APPLICATION Ensure all surfaces are clean dry and free from loose matter. Premseal Primer can be applied by brush or roller. Ensure that Premseal Primer is fully dry before application of membrane.

| TYPICAL PROPERTIES | TEST METHOD | DATA |
|--------------------|-------------|----------------------------|
| Viscosity | Cup No 4 | 60-64 Secs |
| Solids Contents | | 47% |
| Flash Point | | >39°C |
| Coverage | | 6 -8 m ² /litre |
| Specific Gravity | | 0.85-0.90 |

| | |
|------------------|----------------|
| PACKAGING | 5 and 25 Litre |
|------------------|----------------|

Note - the Typical Data shown in this leaflet is intended as a general guide and is based on tests carried out under controlled conditions. For further information on Product Specification consult Premier Coatings Ltd.