



www.premiercoatings.com

PRODUCT DATA SHEET

Headcorn Road · Smarden · Ashford · Kent · TN27 8PJ · United Kingdom
Telephone: + 44 (0) 1233 770 663 · Fax: + 44 (0) 1233 770 633
E-mail: enquiries@premiercoatings.com

PREMSEAL REINFORCING TAPE

USES

Used as part of the Premseal Waterproofing system for the reinforcement of edge and corner details.

TYPICAL PROPERTIES

PROPERTY	TEST METHOD	UNITS	DATA
DIMENSIONS			
Backing Thickness	-	mm	0.10
Backing Type	-	-	HDPE
Adhesive Thickness	-	mm	1.40
Total Thickness	-	mm	1.50
Width	-	mm	300
Length	-	m	20
Weight	-	kg/m ²	1.7
MECHANICAL PROPERTIES			
Membrane Strength	ASTM D1000	N/mm	5.0
Elongation	ASTM D1000	%	300
Puncture Resistance	ASTM E154	N	230
Adhesion (180° Peel)	ASTM D1000	N/mm	4.0
FUNCTIONAL DATA			
Water Vapour Transmission	ASTM E96	g/m ² /24h	0.30
Water Penetration % Joint	MOAT 27 5.1.4		Nil
Dimensional Stability	MOAT 27 5.1.6 (80°C)	%	
Longitudinal			-0.1
Lateral			-0.2

Note - The Typical Data shown in this leaflet is intended as a general guide and is based on tests carried out under controlled conditions. For further information on Product Specification consult Premier Coatings Ltd.