

Premier ButylTM P16HT Primer

Primer for use with Premier ButylTM Tapes

Composition

Premier ButylTM P16HT Primer is comprised of adhesive in hydrocarbon solvent.

Uses

Premier ButylTM P16HT Primer is used as primer for Premier ButylTM tape systems.

Application

See *Instructions for Use* for further details.

Storage conditions

Store Premier ButylTM P16HT Primer in a cool (+0°C to +30°C), dry place, in original packaging.

Waste material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

Typical properties

Colour	Black
Density	0.78 g/cm ³
Total solids	25%
Flash Point	-12°C
Consumption	4 m ² /l
Saponification value	<10 mg KOH/g
VOC	600 g/l
Shelf life	2 years

Important: Premier Coatings Ltd. pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Premier Coatings Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. Q09303) and an Environmental Management System registered to BS EN ISO 14001 (BSI Certificate no. EMS 67780).